

to receive a list of at least two control point addresses to which a service request can be sent and to send a service request to a control point address selected on the basis of the congestion information

**REMARKS**

The above preliminary amendment is made to insert an abstract page into the application and to amend claims 1-22.

Applicant respectfully requests that this preliminary amendment be entered into the record prior to calculation of the filing fee and prior to examination and consideration of the above-identified application.


If a telephone conference would be helpful in resolving any issues concerning this communication, please contact Applicant's attorney of record, Michael B. Lasky at 952-912-0527.

Respectfully submitted,

Altera Law Group, LLC  
6500 City West Parkway, Suite 100  
Minneapolis, MN 55344-7701  
(952) 912-0527

Date: June 1, 2001

By:

  
\_\_\_\_\_  
Michael B. Lasky  
Reg. No. 29,555  
MBL/jsa

**Appendix A**  
**Marked Up Version of the Amended Claims**

1. (AMENDED) Method of initiating services in a telecommunications network including at least one switching point [(SSP)] and at least two control points [(SCP1, SCP2, SCP3)] for controlling services, which control points each have a unique address, in which method a service request is sent by the switching point [(SSP)] to the control point [(SCP)] in order to initiate a service, [c h a r - a c t e r i z e d in that] the method comprising

at least two control point addresses are set to which a service request can be sent and

a service request is sent to the control point addresses set one at a time, until the service is initiated at one of the addresses.

2. (AMENDED) Method according to claim 1, [c h a r a c t e r i z e d in that] wherein

the service request is sent to one address [(SCP1)] and

when this address does not initiate the service, the service request is sent to another address [(SCP2)], until the service is initiated at one of the addresses.

3. (AMENDED) Method according to claim 2, [c h a r a c t e r i z e d in that] wherein

at least one control point [(SCP1)] provides the switching point [(SSP)] with congestion information,

the service request is sent to one address selected on the basis of the congestion information, and

when this address does not initiate the service, the service request is sent to another address selected on the basis of the congestion information, until the service is initiated at one of the addresses.

4. (AMENDED) Method according to claim 1, [c h a r a c t e r i z e d in that] wherein

the telecommunications network is an intelligent network and

the addresses are set in the trigger data of IN-services.

5. (AMENDED) Method according to claim 2, [c h a r a c t e r i z e d in that] wherein

a priority indication is attached to the addresses set and

another address is selected on basis of the priority indication.

6. (AMENDED) Method according to claim 2, [3, or 4, c h a r a c t e r i z e d in that] wherein the service request is sent to another address when the previous address does not respond.

7. (AMENDED) Method according to claim 2, [3, or 4, c h a r a c t e r i z e d in that] wherein the service request is sent to another address when the previous address refuses to initiate the service.

8. (AMENDED) Method according to [any one of] claim[s] 1[ - 5, c h a r a c t e r i z e d in that] wherein the re-sending of the service request is controlled by a limit.

9. (AMENDED) Method of initiating services in a telecommunications network including at least one switching point [(SSP)] and at least two control points [(SCP1, SCP2, SCP3)] for controlling services, which control points each have a unique

09071862-060101

address, in which method a service request is sent by the switching point [(SSP)] to the control point [(SCP)] in order to initiate a service, and the switching point [(SSP)] has congestion information of at least one control point [(SCP), c h a r a c t e r i z e d in that] the method comprising:

at least two control point addresses are set to which a service request can be sent and

a service request is sent to a control point address selected on the basis of the congestion information.

10. (AMENDED) Method according to claim 9, [c h a r a c t e r i z e d in that] wherein the congestion information is sent by at least one control point [(SCP1)], which congestion information restricts the rate at which service requests are sent to this control point [(SCP1)].

11. (AMENDED) Method according to claim 9, [c h a r a c t e r i z e d in that] wherein the congestion information is based on the number of service requests sent by the switching point [(SSP)] to the control point [(SCP)].

12. (AMENDED) Method according to claim 10, [c h a r a c t e r i z e d in that] wherein the address which still has free capacity according to the congestion information is selected.

13. (AMENDED) Method according to claim 9, [10 or 11, c h a r a c t e r i z e d in that] wherein the address which has the least restricting congestion information is selected.

14. (AMENDED) Method according to claim 9, [c h a r a c t e r i z e d in that] wherein

the service request is sent to one address selected on the basis of the congestion information and

when this address does not initiate the service, the service request is sent to another address selected on the basis of the congestion information, until the service is initiated at one of the addresses.

15. (AMENDED) Method according to claim 14, [c h a r a c t e r i z e d in that] wherein

a maximum number for initiation attempts is set,

it is checked whether the service is initiated at the latest address,

it is checked whether the maximum number of initiation attempts is reached,

and

the service request is sent to another address selected on the basis of the congestion information, until the result of one of the checks is "true".

16. (AMENDED) Method according to claim 14 [or 15, c h a r a c t e r i z e d in that] wherein the service request is sent to another address when the previous address does not respond.

17. (AMENDED) Method according to claim 14 [or 15, c h a r a c t e r i z e d in that] wherein the service request is sent to another address when the previous address refuses to initiate the service.

18. (AMENDED) Method according to claim 9, [c h a r a c t e r i z e d in that] wherein

the telecommunications network is an intelligent network and

the addresses are set in the trigger data of IN-services.

19. (AMENDED) A telecommunications network including at least one switching point [(SSP)], at least two control points [(SCP1, SCP2, SCP3)] for controlling services, which control points each have a unique address, and a database for storing information relating to services, in which network the switching point [(SSP)] sends a service request to the control point [(SCP)] in order to initiate a service,

[c h a r a c t e r i z e d in that] wherein

in the database, at least two control point addresses are stored to which a service request can be sent and

the switching point [(SSP)] is adapted to send a service request to the set control point addresses one at a time, until the service is initiated at one of the addresses.

20. (AMENDED) A switching point for a telecommunications network including at least one switching point [(SSP)], at least two control points [(SCP1, SCP2, SCP3)] for controlling services, which control points each have a unique address, and a database for storing information relating to services, in which network the switching point [(SSP)] sends a service request to the control point [(SCP)] in order to initiate a service,

[c h a r a c t e r i z e d in that] wherein the switching point [(SSP)] is adapted

to receive a list of at least two control point addresses to which a service request can be sent and

to send a service request to the set control point addresses one at a time, until the service is initiated at one of the addresses.

21. (AMENDED) A telecommunications network including at least one switching point [(SSP)], at least two control points [(SCP1, SCP2, SCP3)] for controlling

services, which control points each have a unique address, and a database for storing information relating to services, in which network the switching point [(SSP)] sends a service request to the control point [(SCP)] in order to initiate a service and the switching point [(SSP)] has congestion information of at least one control point [(SCP)],

[c h a r a c t e r i z e d in that] wherein

in the database, at least two control point addresses are stored to which a service request can be sent and

the switching point [(SSP)] is adapted to send a service request to a control point address selected on the basis of the congestion information.

22. (AMENDED) A switching point for a telecommunications network including at least one switching point [(SSP)], at least two control points [(SCP1, SCP2, SCP3)] for controlling services, which control points each have a unique address, and a database for storing information relating to services, in which network the switching point [(SSP)] sends a service request to the control point [(SCP)] in order to initiate a service and the switching point [(SSP)] has congestion information of at least one control point [(SCP)],

[c h a r a c t e r i z e d in that] wherein the switching point [(SSP)] is adapted

to receive a list of at least two control point addresses to which a service request can be sent and

to send a service request to a control point address selected on the basis of the congestion information.

09371362-050101  
TOT090-29372860